

NEW PRODUCT CATALOGUE 2024-2025



AFFORDABILITY MEETS DURABILITY



Innovation never stops

Guided by Japanese design principles, every element of our product is chosen to improve performance, balance, usability, longevity & control. Attention to details that ensures the professional in finishing every single job as easy as possible. That's what drives us & keeps us one step ahead.


Safety

Double-Insulation power tool, indicated by the double square mark (◻◻) can be operated without external grounding. All HiKOKI power tools are designed and manufactured considering safety and usability.


General precautions

1. Read and follow handling instructions provided with the power tool and comply with all the operating instructions and warnings.
2. Never let children use the power tool.
3. Keep others, especially children, away from the tool.
4. Wear eye protector to protect the eyes.
5. Never touch blades or cutters during operation.
6. Avoid unintentional contact with the power switch when the tool is connected to a power source.
7. To ensure proper function of the tool, DO NOT remove installed covers or screws. DO NOT modify components and parts.
8. Prior to operation, carefully inspect the tool to ensure all the parts properly functioning.
9. Immediately stop operation if abnormalities are noted.
10. Ensure that motor ventilation opening is kept fully open.
11. Always keep the blades and cutters sharp and clean.
12. Have the power tool inspected at a proper regular interval by an authorized Service Center.
13. Maintain the proper care and cleanliness of the power tool.
14. Consult an authorised Service Center for repair and/or part replacement.
15. DO NOT use the power tool for any other application than those specified in the handling instructions.
16. DO NOT use the tool for work beyond its prescribed capability.
17. To avoid possible electric shock, DO NOT use the power tool in wet areas.
18. Ensure that the applied voltage is the same as that specified on the nameplate.
19. Ensure that electric plug is plugged into a matching receptacle that is properly installed and grounded in accordance with the instruction manual, all applicable local codes, and ordinances, except for double insulated tools.
20. Ensure that the power supply is disconnected after operation.
21. DO NOT lift the power tool with the cord or remove the plug from the receptacle by pulling the cord.
22. Always handle the power tool with care.
23. Proper posture is essential for safe operation.
24. Dress properly and work in proper clothing and shoes.
25. Always keep the work area in good order.
26. When not in use, store the power tool.
27. DO NOT stare into LASER beam.

Icons





	Drill	1
	Impact Drill	1
	Disc Grinder	2
	Die Grinder	3
	Hammer Drill	4
	Demolition Hammer	4
	Marble Cutter	5
	Trimmer	6
	Planer	6
	Cut-off Machine	7
	Polisher	7
	Blower	8
	Heat Gun	9

6.5mm
Drill
HMD 6A



Specifications

HMD6A	
Capacity	Wood Maxø 15 mm
	Steel Maxø 6.5 mm
Power Input	320 w
No-Load Speed	0 - 4,200 /min.
Overall Length	210 mm
Weight	0.9 kg

Features

- Variable Speed Control Switch.
- Reversible Running.

MRP: 2,750/-



13mm
Impact Drill
HMDV 13A



Specifications

HMDV 13A	
Capacity	Concrete 13 mm
	Steel 13 mm
	Wood 25 mm
Full Load Impact Rate	48,000 /min.
Power Input	550 w
No-Load Speed	0 - 3,000 /min.
Overall Length	295 mm
Weight	1.8 kg

Features

- Powerful Motor
- Soft Grip For Comfort Operation.

MRP: 3,900/-



100mm

Disc Grinder

HMG 10A



Specifications

HMG 10A	
Wheel Dia.	100 mm
Spindle Thread	M10
Power Input	600w
No-Load Speed	12000 /min
Overall Length	271 mm
Weight	1.7 kg

Features

- Slide Switch.
- Compact & Light Weight.

MRP: 3,000/-



125mm

Disc Grinder

HMG 13A



Specifications

HMG 13A	
Wheel Dia.	125 mm
Spindle Thread	M14
Power Input	880w
No-Load Speed	11,000 /min
Overall Length	271 mm
Weight	1.8 kg

Features

- Slide Switch.
- Compact & Light Weight.

MRP: 4,025/-



180mm

Disc Grinder

HMG 18A



Specifications

HMG 18A	
Wheel Diameter	180mm
Spindle Thread	M14
Power Input	2,600w
No-Load Speed	8,400/min
Overall Length	485mm
Weight	5.8 kg

Features

- 2,600W High Power
- Trigger Switch

MRP: 8,700/-



25mm

Die Grinder

HMGP 3A



Specifications

HMGP 3A	
Wheel Dia.	25mm
Hand Capacity	6mm
Power Input	550w
No-Load Speed	34,000/min
Overall Length	379mm
Weight	1.7kg

Features

- 6mm Collet With Snap Switch.
- Longer Nose To Reach, In Depth Deburring.
- High Speed Motor.

MRP: 5,175/-



20mm

Hammer Drill

HMDH 20A



Specifications

HMDH 20A	
Capacity	Concrete 20mm
	Steel 13mm
	Wood 32mm
Power Input	550w
Bit Shank	SDS plus
No-Load Speed	0-1,250/min
Weight	2.6Kg

Features

- 2 Mode With Variable Speed.
- Equipped With 550w Motor.
- Compact & Light Weight.

SDS plus Shank

MRP: 6,600/-



25mm

Demolition Hammer

HMGP 3A



Specifications

HMGP 3A	
Power Input	1,500 w
Impact Rate	1,000 - 2,050/min
Overall Length	594 mm
Weight	10.6kg

Features

- 2 Mode With Variable Speed.
- Equipped With 550w Motor.
- Compact & Light Weight.
- Soft Grip Handle.

SDS plus Shank

MRP: 24,000/-



110mm

Marble Cutter

HMCM 4A



Specifications

HMCM 4A	
Wheel Dia.	110mm
Max. Cutting Depth	32mm
Power Input	1,300w
No-Load Speed	13,000/min
Overall Length	215.5mm
Weight	3.1kg

Features

- Powerful Motor.
- Dust Proof Switch.

MRP: 5,100/-



125mm

Marble Cutter

HMCM 5A



Specifications

HMCM 5A	
Wheel Dia.	125mm
Max. Cutting Depth	39mm
Power Input	1,400w
No-Load Speed	12,000/min
Overall Length	223.5mm
Weight	3.2kg

Features

- Powerful Motor.
- Dust Proof Switch.

MRP: 5,450/-



Trimmer

HMM 6A



Specifications

HMM 6A	
Collet Chuck	6.35 mm
Power Input	505 w
No-Load Speed	32,000 /min.
Overall Length	207 mm
Weight	1.5 kg

Features

- Fine Bit Depth Adjustment.

MRP: 5,200/-



80mm

Planer

HMP 20A



Specifications

HMP 20A	
Cutting Width	80 mm
Max. Cutting Depth	1.0 mm
Power Input	560 w
No-Load Speed	16,500 /min
Overall Length	300 mm
Weight	2.6 kg

Features

- Larger Trigger For Comfortable & Easy Operation.
- Robust Aluminium End Bracket.

MRP: 5,700/-



355mm

Cut-Off Machine

HMCC 14A



Specifications

HMCC 14A	
Wheel Diameter	355mm
Power Input	2,200w
No-Load Speed	4,200/min
Dimension (LxWxH)	570x290x610mm
Cutting Angle	0~45°
Weight	14.8kg

Features

- 2,200W High Power.
- Quick-locking Vise.
- Spindle Lock.

MRP: 12,500/-



180mm

Polisher

HMSP 18A



Specifications

HMSP18A	
Capacity: Sanding Disc	180mm
Power Input	1,200w
Spindle Thread	M14
No-load Speed	600-3,300/min
Dimension (LxWxH)	420x116x93mm
Net Tool Weight	2.9kg
Standard Accessories	Real woolen pad, Polishing pad, G-type Handle, Wrench

Features

- 600-3,300/min Variable Speed Control.
- Spindle lock for easy changing of accessories

MRP: 9,300/-



550W

Blower

HMRB 30A



Specifications

HMRB 30A	
Air Velocity (with Nozzle)	0 - 89 m/s
Volume Flow (without Nozzle)	0 - 3.4 m ³ /min
Power Input	550 w
No - Load Speed	0 - 16,000 /min.
Overall Length	493 mm
Weight	1.7 kg

Features

- Variable Speed With Dial Control.



MRP: 3,800/-



500W

Blower

HMRB 30B



Specifications

HMRB 30B	
Power Input	500 w
Air Velocity	89 m/sec
Air Flow	3.4 m ³ /min
No-load Speed	16,000 /min
Dimension (LxWxH)	493x185x184 mm
Net Tool Weight	1.7 kg

Features

- Convenient trigger switch for easy operation.
- Powerful airflows for efficient work.

MRP: 2,722/-



2,000W

Heat Gun

HMRH 600A



Specifications

HMRH600A	
Voltage	230v
Power Input	2,000w
Air Flow	300/500L/min (2-stage switch)
Temperature	450/600°C
Power Cord Length	2m
Dimension (LxWxH)	220x80x234mm
Net Tool Weight	0.45kg
Standard Accessories	Nozzle(round), Nozzle(flat)

Features

- 2-stage Air Flow and Temperature Control.
- Compact and Lightweight for Ease of Use.

MRP: 2,269/- 



HiKOKI

HIGH PERFORMANCE POWER TOOLS



Head Quarters:

Koki Holdings Co., Ltd.

Shinagawa intercity Tower A, 20th Floor, 15-1
Konan 2-chrome, Minato-ku, Tokyo 108-6020
Japan.

Tel; +81-3-5783-0601

Fax: +81-3-5783-0709

Website: www.hikoki-powertools.com

BRANCHES

Ahmedabad	: 90999 20372	Guwahati	: 98360 92333
Bangalore	: 90083 04461	Hyderabad	: 98487 12443
Bhubaneshwar	: 98302 00254	Jaipur	: 88240 99593
Chennai	: 99620 92519	Kolkata	: 98311 60116
Cochin	: 95677 61040	Lucknow	: 90267 53265
Delhi	: 97119 18942	Ludhiana	: 76250 01093
Gurgaon	: 97111 92658	Mumbai	: 75960 26989
		Pune	: 97027 86342

Registered & Head Office:

HiKOKI Power Tools India Pvt. Ltd.

No.11, Old No.9A, 1st Main Road, KIADB Peenya 1st Stage,
Bengaluru, Bengaluru Urban - 560058, Karnataka, INDIA.

Tel: 080 - 4117 0777/78 / 2839 6198

Fax: 080 - 4117 1222

Email: ho.mktg@hikoki-powertools.in

WebSite: www.hikoki-powertools.in



For any Customer Support / Service

Toll Free Number

18005725726

Timings: 10am to 6pm

Closed on Saturdays / Sundays and Public holidays.

Authorised distributor :