



999054 🗰

Features

- 345Nm Tightening Torque
- 600Nm Nut Busting Torque
- Variable Speed Control
- 4-Stage Tightening Mode Selector
- IP56 Dust & Water Resistant
- Bright LED Light
- Compact, Light weight & Well balanced



HIKOKI POWER TOOLS INDIA PVT LTD

E: ho.mktg@hikoki-powertools.in, Website: www.hikoki-powertools.in

Customer Care 1800 5725 726



Auto Stop Modes Prevent Over-tightening

The tool comes with four Auto-Stop modes for a variety of applications and will stop after a preset amount of time has passed to prevent over-tightening of bolts.

	1	2	3	4
Indicator Lamp				
Maximum Unloaded Speed	1,200 / min	1,800 / min	2,400 / min	2,800 / min
Auto Stop Time	Approx. 0.5 sec.			Approx. 1.0 sec.
Uses (For temporary tightening etc.)	Small diameter bolts	Vehicles wheel nut or piping	Heavy machinery or steel frame	

The correct tightening torque depends on the material, size and class of the bolt. Make a test fastening to adjust the mode setting to suit the bolt.

Reverse Rotation Auto-Slow Function to Suppress the Dropping of Nuts

It assists in preventing dropping nuts by automatically stopping at the set time, or automatically changing speed to the designated rotation speed.

* Effective only when the switch is pulled to the maximum extent.

IP56 Dust and Water Resistant*



Thanks to the unique design of dust-protective cooling windows and fully plastic coating on some important inner parts, this product conforms to IP56 protection class ratings (dust and water resistance) for electrical equipment as stipulated by the international IEC regulations.

* The equipment has been designed to withstand the effects of dust and water, but there is no guarantee that it will not malfunction. Do not use or leave the equipment in locations where it is subject to excessive amounts of dust, or in locations where it is submerged in water or subject to rainwater. (Only the main unit conforms to the IP56 protection class ratings when equipped with a battery.)

Customer Care 1800 5725 726



Specifications					
Capacity	Ordinary Bolt	M10-M20			
Capacity	High Tension Bolt	M10-M16			
Square Drive 12.7mm					
Tightening Torque	345Nm	Nm			
Battery Voltage		18V			
	Mode 4	0 - 2,800 / min			
No-load	Mode 3	0 - 2,400 / min			
rotation speed	Mode 2	0 - 1,800 / min			
	Mode 1	0 - 1,200 / min			
Full Load Impact	Rate	0-3,200/min			
Overall Length	144mm				
Weight	1.3kg (Without battery) 2.3kg (BSL36B18X)				
Standard Accessories*2 Batteries (BSL1850MA), Charger(UC18YFSL), Battery Cover, Carry case					

MRP: ₹ 43,365/-



*Standard accessories may vary by country or area



HIKOKI POWER TOOLS INDIA PVT LTD E: ho.mktg@hikoki-powertools.in, Website: www.hikoki-powertools.in Customer Care 1800 5725 726