

FIND YOUR POWER

WITH THE HiKOKI RANGE OF PRODUCTS



HiKOKI
 UNLEASH the NEXT

Registered & Head Office

HiKOKI POWER TOOLS INDIA PVT. LTD.

Plot No.9A, 1st Phase, Peenya Industrial Area, Peenya
 Bangalore – 560 058. India
 Tel: (080) 4117 0777/4117 0778, Fax: 41127 1222

Email: ho.mktg@hikoki-powertools.in | www.hikoki-powertools.in
 (Formerly known as Hitachi Koki India Private Limited)

Head Quarters

Koki Holdings Co., Ltd.

Shinagawa Intercity Tower A, 20th Floor, 15-1
 Konan 2-Chrome, Minato-ku, Tokyo 108-6020, Japan.
 Tel: 81-3-5783-0601, Fax: 81-3-5783-0709

Branches

- Ahmedabad : 079 - 2685 8008
- Bengaluru : 080 - 4117 0777
- Chennai : 044 - 2432 8681 / 2435 0111
- Cochin : +91 - 95677 61040
- Delhi : 011 - 2589 8448 / 4752 8944
- Hyderabad : 040 - 4013 8207
- Jaipur : +91 - 88240 99593
- Bhubaneshwar : +91 - 9778517029
- Kolkata : 033 - 2479 7542
- Lucknow : +91 - 9026753265
- Ludhiana : +91 - 85910 91138
- Mumbai : 022 - 2775 8814
- Pune : +91 - 97027 86342

Impact Drill DV10VST



Impact Drill Tool Kit DV10VST



Forward and reversible for convenience

Soft grip for easier handling

Variable speed trigger to suit multiple drilling applications



28 piece Accessory kit for various applications

Specifications

Impact Drill DV10VST	Unit	
Drill Chuck	-	10 mm keyed
Capacity(Concrete)	mm	10
Power input	w	550
No Load Speed	/min	0-3000
Switch Type	Reverse	Yes
	Variable	Yes
Housing Structure	-	Clam Shell
Soft Grip handle	-	Yes
Dimension (L*W*H)	-	(290*66*200) mm
Package	-	Carton
Standard Accessories	Side handle	Yes
	Depth Gauge	Yes
Weight	KG	1.7

Specifications

Tool Kit DV10VST	Unit	
Drill Chuck	-	10 mm keyed
Capacity(Concrete)	mm	10
Power input	w	550
No Load Speed	/min	0-3000
Switch Type	Reverse	Yes
	Variable	Yes
Housing Structure	-	Clam Shell
Soft Grip handle	-	Yes
Dimension (L*W*H)	-	(290*66*200) mm
Package	-	BMC
Standard Accessories	Side handle	Yes
	Depth Gauge	Yes
	Accessory Kit	Yes
Weight	KG	1.7

Cut Off Machine - CC14STA



Cut Off Machine with soft start - CC14STDU



Quick-lock vise
for fast, precise clamping
of materials



Lightweight* design
with a powerful motor

Spindle lock
for fast and easy wheel
changes

Quick-lock vise
for fast, precise clamping
of materials



Ergonomically design
Comes with a D-shaped handle
for a more comfortable hand position

Spindle lock
for fast and easy wheel
changes

**Spark
Diversion guard**

Specifications

Cut Off Machine - CC14STA	Unit	
Power input	w	2000
Cut Off Wheel Dia	mm	355
Handle Type	-	Bar
No Load Speed	-	3800
Dimension (L*W*H)	-	(584*287*597)mm
Standard Accessories	Cut off Wheel & Wrench	Yes
Weight	KG	14.1

Specifications

Cut Off Machine with soft start CC14STDU	Unit	
Power input	w	2200
Cut Off Wheel Dia	mm	355
Handle Type	-	D type
No Load Speed	-	3800
Soft Start	-	Yes
Dimension (L*W*H)	-	(590*300*650)mm
Standard Accessories	Cut off Wheel & Wrench	Yes
Weight	KG	17

Chipping Hammer Hex Shank 5 Kg - H41SST



Specifications

Chipping Hammer Hex Shank 5 Kg - H41SST		Unit
Shank	-	Hex
Impact energy : EPTA	J	7.2
Power input	w	1010
Full Load Impact Rate	/min	2900
Anti-Vibration Handle	-	Yes
Soft Grip handle	-	Yes
Dimension (L*W*H)	-	(484*96*242)mm
Package	-	BMC
Standard Accessories	Blow Mold Case	Yes
	Bull Point	Yes
	Flat Chisel	Yes
	Side handle	Yes
	Hex Wrench	Yes
Weight	Grease Tube	Yes
		KG

New 14" Cut Off Wheels



New Economy Range - 14" cut-off wheel - 3mm - 796190



Features

- Suitable for Cutting mild steel rods, pipes, channels & TMT bars et.
- Causes less material loss, burnt mark, less burr with better finish

Specifications

New Economy Range - 796190	Unit
Diameter (mm)	355
Arbor Hole (mm)	25.4
Thickness (mm)	3
Shape	Flat Center
Specification	A30QBF
Inner Package	25pcs/pack

New INOX- 14" cut-off wheel - 2.8mm - 796195



Features

- Stainless application - INOX CLEARCUT
- Provides high cutting rate with faster speed

Specifications

New INOX - 796195	Unit
Diameter (mm)	355
Arbor Hole (mm)	25.4
Thickness (mm)	2.8
Shape	Flat Center
Specification	A36QBF
Inner Package	25pcs/pack